radwag.com

C315.6/15.D-1 Baby Scale

WM-001-1010

More information on the website
mirror.radwag.com/en/info,w1,0RI



The drawings, photos and graphics used are for illustrative purposes only.

Functions

Internal battery

Peak hold

GLP Procedures

ALIBI Memory

Datasheet

Metrological parameters	
Maximum capacity [Max]	6 / 15 kg
Readability [d]	2 / 5 g
Tare range	-15 kg
OIML Class	III
Physical parameters	
Display	4.3” LCD (backlit)
Packaging dimensions W x D x H	600×520×180 mm
Net weight	3.5 kg
Gross weight	5.5 kg

Communication interface	
Communication interface	RS232
Electrical parameters	
Power supply	100 – 240 V AC 50/60 Hz and battery
Power consumption max.	5 W
Operation time on batteries	up to 8 h
Environmental conditions	
Operating temperature	0 – +40 °C
Relative humidity	10% – 85% RH no condensation

According to MDR regulations, this scale is not a medical device.

Additional fee for verification

Accessories (Additional Fee)

Power Adapters
RS 232 cables (scale - printer)
Cigarette lighter receptacle power supply cables
Displays
RS 232, RS 485 cables
RS 232 – Ethernet Converter
RS 232 – USB Converter
RS 232 – RS 485 Converter
Receipt Printer

Software (Additional Fee)

• RAD Key [WX-010-0005]
• Scale Editor 2.1 [WX-010-0173]
• R-Lab [WX-010-0080]

Device dimensions W x D x H

